

Female Header

Single / Dual Row; SMT Type

Pitch:1.27mm


Series

47U 12

Odia 奥比亚

Tel: (+86)0755-28248661/2/3

Fax: (+86)0755-27857873







SPECIFICATIONS (技术参数):

Current Rating (额定电流): 1.0 A
 Withstand Voltage (耐压值): 600V AC/Min
 Insulation Resistance (绝缘电阻): 1000MΩ Min
 Contact Resistance (接触电阻): 30mΩ Max
 Operation Temperature (工作温度): -40°C to +105°C

MATERIALS (材质):

Contact Material (接触件材质): Phosphor Bronze of Brass
 Contact Plating (接触件电镀): Gold or Tin over 50u"Ni
 Insulator (绝缘体材质): PBT OR PA6T(UL94V-0)



H = 2.0mm
 H = 3.4mm
 H = 4.3mm
 H = 4.4mm

Ordering Code

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩
 47U 12 4 2 50 M 1 4 1 0

- ① Series No.:
47U = Female Header
- ② Pitch: 12 = 1.27mm
- ③ Insulator Height:
2 = 2.0mm
3 = 3.4mm
4 = 4.3mm
5 = 4.4mm

- ④ Number of row:
1=Sing row
2=Double row
- ⑤ Number of Contacts:
Single row=01(1x1)to 50(1x50)
Double row=04(2x2)to 100(2x50)
- ⑥ Tail & Mounting Style:
M=Straight SMT type

- ⑦ Contact Plated
0=Tin
1=Gold Flash
2=Gold 3u"
3=Gold 5u"
4=Gold 10u"
5=Gold 15u"
6= Gold 30u"
A=Gold 1.5u"
B=Gold 2u"

- ⑧ Material Type
0=PPS
1=PBT
2=LCP
3=Nylon-9T
4=Nylon-6T
5=PA46
- ⑨ Color: 1=Black
- ⑩ Customer Request