

Female Header Pitch:1.27mm/1.27x2.54mm
Single / Dual Row - Straight DIP Type

Series


47Y 12

47Y 13

Odia 奥比亚

Tel: (+86)0755-28248661/2/3

Fax: (+86)0755-27857873




SPECIFICATIONS (技术参数):

Current Rating (额定电流): 1.0 A
Withstand Voltage (耐压值): 600V AC/Min
Insulation Resistance (绝缘电阻): 1000MΩ Min
Contact Resistance (接触电阻): 30mΩ Max
Operation Temperature (工作温度): -40℃ to +105℃






MATERIALS (材质):

Contact Material (接触件材质): Phosphor Bronze of Brass
Contact Plating (接触件电镀): Gold or Tin over 50u"Ni
Insulator (绝缘体材质): PBT OR PA6T(UL94V-0)

47Y13



47Y12



Ordering Code

①②③④⑤⑥⑦⑧⑨⑩
47Y12 6 1 08 S 1 4 1 0

① Series No.:
47Y

② Pitch: 12= 1.27 (Single row)
13= 1.27 x 2.54 (Double row)

③ Insulator Height:
6= 4.6 / 7=5.7 / 8=8.5

④ Number of row:
1=Sing row
2=Double row

⑤ Number of Contacts:
Single row=01(1x1)to 50(1x50)
Double row=04(2x2)to 100(2x50)

⑥ Tail & Mounting Style:
S=Straight DIP type

⑦ Contact Plated
0=Tin
1=Gold Flash
2=Gold 3u"
3=Gold 5u"
4=Gold 10u"
5=Gold 15u"
6= Gold 30u"
A=Gold 1.5u"
B=Gold 2u"

⑧ Material Type
0=PPS
1=PBT
2=LCP
3=Nylon-9T
4=Nylon-6T
5=PA46

⑨ Color: 1=Black

⑩ Customer Request